

1210 DRAYTON PARKING IMPROVEMENTS
FOR JEFF NOTRICA
CITY OF SAVANNAH, CHATHAM COUNTY, GEORGIA
DATE: SEPTEMBER 6, 2024

SHEET INDEX:
DESCRIPTION

1. EXISTING CONDITIONS & DEMOLITION PLAN
2. SITE PLAN
3. GRADING PLAN
4. EROSION CONTROL PLAN
5. DETAILS
6. PRE-DEVELOPED BASIN MAP
7. POST-DEVELOPED BASIN MAP
8. LANDSCAPE PLAN
9. LANDSCAPE DETAILS

SHEET

SHEET C100
SHEET C200
SHEET C300
SHEET C400
SHEET C500-C501
SHEET C600
SHEET C601
SHEET L100
SHEET L101

DRAWING LEGEND

DESCRIPTION	PROPOSED	EXISTING
SANITARY SEWER		--SS--
UNDERGROUND WATER LINE		- - -W - - -
FORCE MAIN		- - -FM - - -
STORM DRAINAGE PIPE		- - - - -
UNDERGROUND TELEPHONE LINE		-T-
UNDERGROUND TELEPHONE CONDUIT		-TC-
UNDERGROUND GAS LINE		- - -12\"/>
DITCH CENTERLINE		- . . - . . -
SPOT ELEVATION		X=90.00
TOP OF CURB ELEVATION		TC=90.00
FIRE HYDRANT		
SEWER MANHOLE		
WATER VALVE		
TELEPHONE MANHOLE		
LIGHT POLE		
SIGN		
WATER METER		
BENCHMARK		
CONCRETE MONUMENT FOUND		
GUY POLE		
IRON PIN FOUND		
IRON PIN SET		
TELEPHONE PEDESTAL		
POWER POLE		
HANDICAP SPACE		
SEDIMENT BASIN MARKER W/NOTCH		

VICINITY MAP

Not To Scale

MINIMUM PROJECT SPECIFICATIONS

ANY JOB DESIGNED BY M.E. SACK ENGINEERING SHALL BE CONSTRUCTED IN ACCORDANCE WITH M.E. SACK ENGINEERING MINIMUM SPECIFICATIONS. IN MUNICIPALITIES WITH THEIR OWN SPECIFICATIONS, THEIR SPECIFICATIONS SHALL SUPERSEDE THE MINIMUM SPECIFICATIONS. LIKEWISE, PROJECTS THAT ARE BID SHALL BE HELD TO THE SPECIFICATIONS WITHIN THE BID DOCUMENT WHICH MAY DIFFER FROM THE MINIMUM SPECIFICATION REQUIREMENTS. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ENSURE THEY HAVE THE APPROPRIATE SPECIFICATIONS FOR EACH PROJECT. OBTAIN THE MINIMUM STANDARDS BY SCANNING THE QR CODE OR CLICKING THIS LINK: <https://www.mesack.com/technical-specification/>

CONTACT ADMIN@MESACK.COM TO REQUEST CONFIRMATION OF CORRECT SPECIFICATIONS AT ANYTIME.

OWNER:
JEFF NOTRICA
P.O. BOX 10027
SAVANNAH, GA 31412
(912) 398-2340
ZANDOR@ME.COM

GPS COORDINATES OF CO:
E: 987670.2413
N: 752061.3541

DATUM: NAVD 88

24 HOUR CONTACT:
MARCUS SACK, P.E.
515 N MAIN ST
HINESVILLE, GA 31313
(912) 368-5212
MARCUS@MESACK.COM

DESIGN PROFESSIONAL:

DATE: 3/17/2025

19
M.E. SACK
ENGINEERING
80

515 NORTH MAIN STREET
P.O. BOX 649
HINESVILLE, GA 31313
TEL: (912) 368-5212

10375 FORD AVENUE
UNIT A-2
RICHMOND HILL, GA 31324

GENERAL NOTES

1. ALL EXISTING UTILITIES SHOWN ARE LOCATED FROM BEST AVAILABLE INFORMATION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ACTUAL FIELD LOCATION AND PROTECTION OF EXISTING UTILITIES. OVERHEAD LINES ARE NOT SHOWN FOR CLARITY.

2. ALL DISTURBED AREAS TO BE REVEGETATED IMMEDIATELY AFTER CONSTRUCTION, IN ACCORDANCE WITH THE MANUAL FOR EROSION AND SEDIMENT CONTROL IN GEORGIA.

3. ALL EROSION AND SEDIMENTATION CONTROL STRUCTURES SHALL BE INSTALLED PRIOR TO THE START OF CONSTRUCTION.

4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REPLACEMENT OF ANY PROPERTY CORNERS, RIGHT OF WAY MONUMENTS, SIGNS OR OTHER STRUCTURES DISTURBED DURING CONSTRUCTION.

5. ALL TRAFFIC AND SIGNAGE CONTROL SHALL BE IN ACCORDANCE WITH THE MANUAL FOR UNIFORM TRAFFIC CONTROL DEVICES, MUTCD, CURRENT EDITION.

REVISION NO.

DATE

DESCRIPTION

1

1/31/2025

CITY OF SAVANNAH REVISIONS 1

2

3/17/2025

CITY OF SAVANNAH REVISIONS 2

JOB NO. 2024-45 PRJ

COVER SHEET

PLOT DATE: March 17, 2025

GEORGIA811®
Utilities Protection Center, Inc.

Know what's below.
Call before you dig.

MARTIN LUTHER KING JR BLVD

MONTGOMERY ST

JEFFERSON ST

BARNARD ST

WHITAKER ST

BULL ST

E PARK AVE

E DUFFY ST

E ANDERSON ST

DRAYTON ST

E HENRY ST

E WALDBURG ST

E BOLTON ST

E GWINNETT ST

E HALL ST

ABERCORN ST

LINCOLN ST

HABERSHAM ST

PRICE ST

E BROAD ST

E 31ST ST

E 31ST LN


E 32ND ST

E 33RD ST

E 34TH ST

E 35TH ST

SITE





1. ZONING = TC-1
2. TOTAL ACRES DEVELOPED = 0.50 AC.
3. TOTAL IMPERVIOUS AREA = 0.37 AC.
0.37 AC, 0.50 AC = 74% IMPERVIOUS
4. UTILITY AND STREET INSTALLATION TO BE IN ACCORDANCE WITH THE CITY OF SAVANNAH STANDARD SPECIFICATIONS.
5. BOUNDARY SURVEY SUPPLIED BY JAMES CRAN BREWER, BREWER LAND SURVEYING, REGISTERED LAND SURVEYOR NO. 3922; TOPOGRAPHICAL SURVEY SUPPLIED BY E.M. SACK ENGINEERING.
6. THIS PARCEL IS IN A ZONE "C" ACCORDING TO THE CHATHAM COUNTY FLOOD MAP COMMUNITY-PANEL NUMBER 13051/01153G, DATED 8/16/2011
7. OFF-STREET PARKING LOT BUFFER:
FOR CITY ORDINANCE THIS BUFFER SHALL BE COMPOSED OF EITHER A MINIMUM THREE (3) FOOT SHADY OPACQUE FENCE OR A MINIMUM THREE (3) FOOT HIGH HEDGE WITH A THREE (3) FOOT WIDE PLANTED AREA.
8. PER CITY OF SAVANNAH STORMWATER CHECKLIST: "CHLORINATED DISINFECTANT WASTE SHALL NOT BE DISCHARGED INTO THE STORMWATER SYSTEM"
9. PER CITY OF SAVANNAH STORMWATER CHECKLIST: THE CITY OF SAVANNAH RESERVES THE RIGHT TO ACCESS THE PROPERTY TO INSPECT STORMWATER FACILITIES.

REVISIONS.	
1	CITY OF SAVANNAH REVISIONS 1
2	CITY OF SAVANNAH REVISIONS 2

THIS DRAWING IS AN INSTRUMENT OF SERVICE AND REMAINS THE PROPERTY OF P.C. SIMONTON & ASSOCIATES, INC. AND M.E. SACK ENGINEERING. IT MAY NOT BE COPIED, ALTERED, OR REPRODUCED IN ANY MANNER WITHOUT PERMISSION ON A SIGNED AND SEALED DOCUMENT. THE INFORMATION CONTAINED HEREIN IS INTENDED FOR THE NAMED CLIENT ONLY. IN THE EVENT OF AN ELECTRONIC VERSION P.C. SIMONTON & ASSOC., INC. AND M.E. SACK ENGINEERING ASSUMES NO RESPONSIBILITY FOR DATA GENERATED, ALTERED OR STAKED FROM THIS DRAWING. IN THE EVENT OF A DISPUTE, HARD COPIES WILL TAKE PRECEDENCE OVER ANY ELECTRONIC MEDIA.*

MARCUS E. SACK
GSWCC LEVEL II # 70248
EXPIRES: 06/14/2026
MARCUS@MESACK.COM

515 NORTH MAIN STREET
P.O. BOX 649
HINESVILLE, GA 31313
TEL: (912) 368-5212



MUNICIPALITY:
SAVANNAH

COUNTY:
CHATHAM

OWNER:
JEFF NOTRICA
P.O. BOX 10027
SAVANNAH, GA 31412
(912) 398-2340
ZANDOR@ME.COM

24 HOUR CONTACT:
MARCUS SACK, P.E.
515 N MAIN ST
HINESVILLE, GA 31313
(912) 368-5212
MARCUS@MESACK.COM


1210 DRAYTON PARKING IMPROVEMENTS

EXISTING
CONDITIONS &
DEMOLITION PLAN

C100

FILE NO: 2024-45

PLOT DATE: March 17, 2025



HANDICAP PARKING NOTES:

1. PER ADA, THE MINIMUM NUMBER OF ACCESSIBLE PARKING SPACES FOR A PARKING LOT WITH 26-50 PARKING SPACES IS 2 ACCESSIBLE SPACES.

REVISIONS:



1	CITY OF SAVANNAH REVISIONS 1
2	CITY OF SAVANNAH REVISIONS 2

"THIS DRAWING IS AN INSTRUMENT OF SERVICE AND REMAINS THE PROPERTY OF P.C. SIMONTON & ASSOCIATES, INC. AND M.E. SACK ENGINEERING. IT MAY NOT BE COPIED, ALTERED, OR REPRODUCED IN ANY MANNER WITHOUT PERMISSION ON A SIGNED AND SEALED DOCUMENT. THE INFORMATION CONTAINED HEREIN IS INTENDED FOR THE NAMED CLIENT ONLY. IN THE EVENT OF AN ELECTRONIC VERSION P.C. SIMONTON & ASSOC., INC. AND M.E. SACK ENGINEERING ASSUMES NO RESPONSIBILITY FOR DATA GENERATED, ALTERED OR STAKED FROM THIS DRAWING. IN THE EVENT OF A DISPUTE, HARD COPIES WILL TAKE PRECEDENCE OVER ANY ELECTRONIC MEDIA."

DESIGN PROFESSIONAL:

MARCUS E. SACK
GSWCC LEVEL II # 70248
EXPIRES: 06/14/2026
MARCUS@MESACK.COM

515 NORTH MAIN STREET
P.O. BOX 549
HINESVILLE, GA 31313
TEL: (912) 368-5212



MUNICIPALITY:
SAVANNAH

COUNTY:
CHATHAM

OWNER:
JEFF NOTRICA
P.O. BOX 10027
SAVANNAH, GA 31412
(912) 398-2340
ZANDOR@ME.COM

24 HOUR CONTACT:
MARCUS SACK, P.E.
515 N MAIN ST
HINESVILLE, GA 31313
(912) 368-5212
MARCUS@MESACK.COM




1210 DRAYTON
PARKING
IMPROVEMENTS

SITE
PLAN


C200


FILE NO: 2024-45





PLOT DATE: March 17, 2025



DESCRIPTION	PROPOSED
SIDEWALK (CONCRETE)	
PAVEMENT (CONCRETE)	







DESCRIPTION	PROPOSED
CONCRETE SIDEWALK	
CONCRETE PAVING/DRIVEWAY	
PERVIOUS BRICK PAVERS	
LANDSCAPING/GRASS	

ALL THE CONCRETE MUST DRAIN. STANDING WATER AND "BIRD BATHS" WILL NOT BE ACCEPTED. IF EXISTING SECTIONS DO NOT DRAIN, THEY MUST BE BROUGHT TO APPROPRIATE LINES AND GRADES TO CREATE POSITIVE DRAINAGE TO THE APPROPRIATE DRAINAGE CONVEYANCE.

DRAWING COMPLETED BY CHRIS HEROLD	REVISONS:
	1 CITY OF SAVANNAH REVISIONS 1
	2 CITY OF SAVANNAH REVISIONS 2
<p>"THIS DRAWING IS AN INSTRUMENT OF SERVICE AND REMAINS THE PROPERTY OF P.C. SIMONET & ASSOCIATES, INC. AND M.E. SACK ENGINEERING. IT MAY NOT BE COPIED, ALTERED, OR REPRODUCED IN ANY MANNER WITHOUT PERMISSION ON A SIGNED AND SEALED DOCUMENT. THE INFORMATION CONTAINED HEREIN IS INTENDED FOR THE NAMED CLIENT ONLY. IN THE EVENT OF AN ELECTRONIC VERSION, C. SIMONET & ASSOCIATES, INC. AND M.E. SACK ENGINEERING ASSUMES NO RESPONSIBILITY FOR DATA GENERATED, ALTERED OR STAKED FROM THIS DRAWING. IN THE EVENT OF A DISPUTE, HARD COPIES WILL TAKE PRECEDENCE OVER ANY ELECTRONIC MEDIA."</p>	

DESIGN PROFESSIONAL:
MARCUS E. SACK
GSWCC LEVEL II # 70248
EXPIRES: 06/14/2026
MARCUS@MESACK.COM

515 NORTH MAIN STREET
P.O. BOX 649
HINESVILLE, GA 31313
TEL: (912) 368-5212

MUNICIPALITY:
SAVANNAH

COUNTY:
CHATHAM

OWNER:
JEFF NOTRICA
P.O. BOX 10027
SAVANNAH, GA 31412
(912) 398-2340
ZANDOR@ME.COM


24 HOUR CONTACT:
MARCUS SACK, P.E.
515 N MAIN ST
HINESVILLE, GA 31313
(912) 368-5212
MARCUS@MESACK.COM

1210 DRAYTON PARKING IMPROVEMENTS

GRADING PLAN

C300

FILE NO: 2024-45
PLOT DATE: March 17, 2025



VICINITY MAP
NOT TO SCALE

DRAYTON ST
(APPROX. 45' R/W)

E DUFFY LN
(R/W UNKNOWN)

N/F
COODY HANNAH
COODY ROBERT

E HENRY ST
(APPROX. 75' R/W)

EXISTING CONDITIONS

THE EXISTING SITE CONSISTS OF AN EXISTING
PARKING LOT AND BUILDINGS. THE MAJORITY OF THE
SITE SLOPES GENTLY TO THE NORTHWEST.

SITE INFORMATION

TOTAL PROPERTY AREA = 0.44 AC.
TOTAL DISTURBED AREA = 0.44 AC
SOIL TYPE = U (URBAN LAND)

CONSTRUCTION ACTIVITY DESCRIPTION

SINGLE PHASE - CONSISTS OF INSTALLING CONSTRUCTION
EXIT, PERIMETER BMPs, DUST CONTROL, GRUBBING, FINE
GRADING, MAINTAIN CONSTRUCTION EXIT AND SILT FENCE.
USE DUST CONTROL, MULCHING, AND TEMPORARY GRASSING
WHERE INDICATED. FINAL GRADING, ONCE PERMANENT
GRASSING IS ESTABLISHED TEMPORARY MEASURES CAN BE
REMOVED INCLUDING SILT FENCE AND CONSTRUCTION EXIT.

SILT STORAGE CALCULATION SITE

ESTIMATED EROSION = 0.44 AC.

0.44 AC. X 67 C.Y. = 29 C.Y. STORAGE CAPACITY REQUIRED

ALL AREAS DRAINED WILL BE CAPTURED BY SILT FENCE TO
PREVENT SILT FROM ESCAPING THE SITE.

DRAWING COMPLETED BY: CHRIS JEROLD



REVISIONS:
1 CITY OF SAVANNAH REVISIONS 1
2 CITY OF SAVANNAH REVISIONS 2

"THIS DRAWING IS AN INSTRUMENT OF SERVICE
AND REMAINS THE PROPERTY OF P.C. SIMONTON
& ASSOCIATES, INC. AND M.E. SACK
ENGINEERING. IT MAY NOT BE COPIED, ALTERED,
OR REPRODUCED IN ANY MANNER WITHOUT
PERMISSION ON A SIGNED AND SEALED
DOCUMENT. THE INFORMATION CONTAINED
HEREIN IS INTENDED FOR THE NAMED CLIENT
ONLY. IN THE EVENT OF AN ELECTRONIC VERSION
P.C. SIMONTON & ASSOC., INC. AND M.E. SACK
ENGINEERING ASSUMES NO RESPONSIBILITY FOR
DATA GENERATED, ALTERED OR STAKED FROM
THIS DRAWING. IN THE EVENT OF A DISPUTE,
HARD COPIES WILL TAKE PRECEDENCE OVER ANY
ELECTRONIC MEDIA."

DESIGN PROFESSIONAL:

MARCUS E. SACK
GSWCC LEVEL II # 70248
EXPIRES: 06/14/2026
MARCUS@MESACK.COM

515 NORTH MAIN STREET
P.O. BOX 649
HINESVILLE, GA 31313
TEL: (912) 368-5212



MUNICIPALITY:
SAVANNAH

COUNTY:
CHATHAM

OWNER:
JEFF NOTRICA
P.O. BOX 10027
SAVANNAH, GA 31412
(912) 398-2340
ZANDOR@ME.COM

24 HOUR CONTACT:
MARCUS SACK, P.E.
515 N MAIN ST
HINESVILLE, GA 31313
(912) 368-5212
MARCUS@MESACK.COM


1210 DRAYTON
PARKING
IMPROVEMENTS

EROSION
CONTROL
PLAN

C400

FILE NO: 2024-45

PLOT DATE: March 17, 2025



GEORGIA UNIFORM CODING SYSTEM

FOR SOIL EROSION AND SEDIMENT CONTROL PRACTICES

GEORGIA SOIL AND WATER CONSERVATION COMMISSION

STRUCTURAL PRACTICES

CODE	PRACTICE	DETAIL	MAP SYMBOL	DESCRIPTION
Cd	CHECKDAM			A small temporary barrier or dam constructed across a swale, drainage ditch or area of concentrated flow.
Ch	CHANNEL STABILIZATION			Improving, constructing or stabilizing an open channel, existing stream, or ditch.
Co	CONSTRUCTION EXIT			A crushed stone pad located at the construction site exit to provide a place for removing mud from tires thereby protecting public streets.
Cr	CONSTRUCTION ROAD STABILIZATION			A gravelway constructed as part of a construction plan including access roads, subdivision roads, parking areas and other on-site vehicle transportation routes.
Dc	STREAM DIVERSION CHANNEL			A temporary channel constructed to convey flow around a construction site while a permanent structure is being constructed.
Di	DIVERSION			An earth channel or dike located above, below or across a slope to divert runoff. This may be a temporary or permanent structure.
Dn1	TEMPORARY DOWNDRAIN STRUCTURE			A flexible conduit of heavy-duty fabric or other material designed to safely conduct surface runoff down a slope. This is temporary and inexpensive.
Dn2	PERMANENT DOWNDRAIN STRUCTURE			A paved chute, pipe, sectional conduit or similar material designed to safely conduct surface runoff down a slope.
Fr	FILTER RING			A temporary stone barrier constructed at storm drain inlets and pond outlets.
Ga	GABION			Rock filter baskets which are hand-placed into position forming soil stabilizing structures.
Gr	GRADE STABILIZATION STRUCTURE			Permanent structures installed to protect channels or waterways where otherwise the slope would be sufficient for the running water to form gullies.
Lv	LEVEL SPREADER			A structure to convert concentrated flow of water into less erosive sheet flow. This should be constructed only on undisturbed soils.
Rd	ROCK FILTER DAM			A permanent or temporary stone filter dam installed across small streams or drainageways.
Re	RETAINING WALL			A wall installed to stabilize cut and fill slopes where maximum permissible slopes are not obtainable. Each situation will require special design.
Rt	RETRO FITTING			A device or structure placed in front of a permanent stormwater detention pond outlet structure to serve as a temporary sediment filter.
Sd1	SEDIMENT BARRIER			A barrier to prevent sediment from leaving the construction site. It may be sandbags, bales of straw or hay, brush, logs and poles, gravel, or a silt fence.
Sd2	INLET SEDIMENT TRAP			An impounding area created by excavating around a storm drain drop inlet. The excavated area will be filled and stabilized on completion of construction activities.
Sd3	TEMPORARY SEDIMENT BASIN			A basin created by excavation or a dam across a waterway. The surface water runoff is temporarily stored allowing the bulk of the sediment to drop out.
Sd4	TEMPORARY SEDIMENT TRAP			A small temporary pond that drains a disturbed area so that sediment can settle out. The principle feature distinguishing a temporary sediment trap from a temporary sediment basin is the lack of a pipe or riser.
Sk	FLOATING SURFACE SKIMMER			A buoyant device that releases/draws water from the surface of sediment ponds, traps, or basins at a controlled rate of flow.
Spb	SEEP BERM			Linear control device constructed as a diversion perpendicular to the direction of runoff to enhance dissipation and infiltration, while creating multiple sedimentation chambers with the employment of intermediate dikes.

STRUCTURAL PRACTICES


CODE	PRACTICE	DETAIL	MAP SYMBOL	DESCRIPTION
Sr	TEMPORARY STREAM CROSSING			A temporary bridge or culvert-type structure protecting a stream or watercourse from damage by crossing construction equipment.
St	STORMDRAIN OUTLET PROTECTION			A paved or short section of riprap channel at the outlet of a storm drain system preventing erosion from the concentrated runoff.
Su	SURFACE ROUGHENING			A rough soil surface with horizontal depressions on a contour or slopes left in a roughened condition after grading.
Tc	TURBIDITY CURTAIN			A floating or staked barrier installed within the water (it may also be referred to as a floating boom, silt barrier, or silt curtain).
Tp	TOPSOILING			The practice of stripping off the more fertile soil, storing it, then spreading it over the disturbed area after completion of construction activities.
Tr	TREE PROTECTION			To protect desirable trees from injury during construction activity.
Vt	VEGETATED WATERWAY OR STORMWATER DRAINAGE CHANNEL			Paved or vegetative water outlets for diversions, terraces, berms, dikes or similar structures.

VEGETATIVE PRACTICES

CODE	PRACTICE	DETAIL	MAP SYMBOL	DESCRIPTION
Bf	BUFFER ZONE			Strip of undisturbed original vegetation, enhanced or restored existing vegetation or the reestablishment of vegetation surrounding an area of disturbance or bordering streams.
Cs	COASTAL DUNE STABILIZATION (WITH VEGETATION)			Planting vegetation on dunes that are denuded artificially constructed, or re-nourished.
Ds1	DISTURBED AREA STABILIZATION (WITH MULCHING ONLY)			Establishing temporary protection for disturbed areas where seedlings may not have a suitable growing season to produce an erosion retarding cover.
Ds2	DISTURBED AREA STABILIZATION (WITH TEMP. SEEDING)			Establishing a temporary vegetative cover with fast growing seedlings on disturbed areas.
Ds3	DISTURBED AREA STABILIZATION (WITH PERM. SEEDING)			Establishing a permanent vegetative cover such as trees, shrubs, vines, grasses, or legumes on disturbed areas.
Ds4	DISTURBED AREA STABILIZATION (SEEDING)			A permanent vegetative cover using sods on highly erodible or critically eroded lands.
Du	DUST CONTROL ON DISTURBED AREAS			Controlling surface and air movement of dust on construction site, roadways and similar sites.
Fl-Cd	FLOCCULANTS AND COAGULANTS			Substance formulated to assist in the solids/liquid separation of suspended particles in solution.
Sb	STREAMBANK STABILIZATION (USING PERM. VEGETATION)			The use of readily available native plant materials to maintain and enhance streambanks, or to prevent, or restore and repair small streambank erosion problems.
Ss	SLOPE STABILIZATION			A protective covering used to prevent erosion and establish temporary or permanent vegetation on steep slopes, shore lines, or channels.
Tac	TACKIFIERS AND BINDERS			Substance used to anchor straw or hay mulch by causing the organic material to bind together.

GoSWCC (Amended - 2013)

CRUSHED STONE CONSTRUCTION EXIT



NOTES:

1. AVOID LOCATING ON STEEP SLOPES OR AT CURVES ON PUBLIC ROADS.
2. REMOVE ALL VEGETATION AND OTHER UNSUITABLE MATERIAL FROM THE FOUNDATION AREA, GRADE, AND CROWN FOR POSITIVE DRAINAGE.
3. AGGREGATE SIZE SHALL BE IN ACCORDANCE WITH NATIONAL STONE ASSOCIATION R-2 (1.5"-3.5" STONE).
4. GRAVEL PAD SHALL HAVE A MINIMUM THICKNESS OF 6".
5. PAD WIDTH SHALL BE EQUAL FULL WIDTH AT ALL POINTS OF VEHICULAR EGRESS, BUT NO LESS THAN 20'.
6. A DIVERSION RIDGE SHOULD BE CONSTRUCTED WHEN GRADE TOWARD PAVED AREA IS GREATER THAN 2%.
7. INSTALL PIPE UNDER THE ENTRANCE IF NEEDED TO MAINTAIN DRAINAGE DITCHES.
8. WHEN WASHING IS REQUIRED, IT SHOULD BE DONE ON AN AREA STABILIZED WITH CRUSHED STONE THAT DRAINS INTO AN APPROVED SEDIMENT TRAP OR SEDIMENT BASIN (DIVERT ALL SURFACE RUNOFF AND DRAINAGE FROM THE ENTRANCE TO A SEDIMENT CONTROL DEVICE).
9. WASHRACKS AND/OR TIRE WASHERS MAY BE REQUIRED DEPENDING ON SCALE AND CIRCUMSTANCE. IF NECESSARY, WASHRACK DESIGN MAY CONSIST OF ANY MATERIAL SUITABLE FOR TRUCK TRAFFIC THAT REMOVE MUD AND DIRT.
10. MAINTAIN AREA IN A WAY THAT PREVENTS TRACKING AND/OR FLOW OF MUD ONTO PUBLIC RIGHTS-OF-WAYS. THIS MAY REQUIRE TOP DRESSING, REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT.

Ds2 SPECIES AND PLANTING SCHEDULE

SPECIES	BROADCAST RATES (1) PER ACRE	PER 1000 Sq.Ft.	PLANTING DATES BY RESOURCE AREAS (3)	REMARKS
RYEGRASS, ANNUAL ALONE	40 lbs.	0.8 lbs.	M-L P C	227,000 SEED PER POUND. DENSE COVER. VERY COMPETITIVE AND IS NOT TO BE USED IN MIXTURES.

Ds3 SPECIES AND PLANTING SCHEDULE

SPECIES	BROADCAST RATES (1) PER ACRE	PER 1000 S.F.	PLANTING DATES BY RESOURCE AREA (3)	AREAS *	SPECIFICATIONS
BERMUDA, COMMON (CYNODON DACTYLON)	10 LBS.	0.2 LB.	P	J F M A M J J A S O N D	1,787,000 SEED PER POUND. QUICK COVER. LOW GROWING AND SOO FORMING. FULL SUN. GOOD FOR ATHLETIC FIELDS.
HILLED SEED ALONE WITH OTHER PERENNIALS	6 LBS.	0.1 LB.	P	J F M A M J J A S O N D	
BERMUDA, COMMON (CYNODON DACTYLON) UNHILLED SEED WITH OTHER PERENNIALS	10 LBS.	0.2 LB.	P	J F M A M J J A S O N D	PLANT WITH WINTER ANNUALS. PLANT WITH TALL FESCUE.
BERMUDA SPRIGS (CYNODON DACTYLON)	40 CU. FT.	0.9 CU.FT.	P	J F M A M J J A S O N D	A CUBIC FT. CONTAINS APPROXIMATELY 850 SPRIGS. A BUSHEL CONTAINS 1.25 CF. OR APPROXIMATELY 800 SPRIGS.
COASTAL, COMMON, MIDLAND, OR TIFT 44	10 LBS.	0.2 LB.	P	J F M A M J J A S O N D	
COASTAL, COMMON, OR TIFT 44	10 LBS.	0.2 LB.	P	J F M A M J J A S O N D	

(1) BROADCAST RATES ARE IN PURE LIVE SEED (PLS)
(2) M-L REPRESENTS THE MOUNTAIN, BLUE RIDGE, AND RIDGES AND VALLEYS MURAS
(3) DARK LINES INDICATE OPTIMUM DATES, GRAY LINES INDICATE PERMISSIBLE BUT MARGINAL DATES.

Ds1 DISTURBED AREA STABILIZATION (W/MULCHING ONLY)

SPECIFICATIONS

A. For temporary protection of critical areas without seeding. This standard applies to grades or cleared areas which may be subjected to erosion for 6 months or less, where seeding may not have a suitable growing season to produce an erosion retardant cover, but which can be stabilized with a mulch cover.

Site Preparation

1. Grade as needed and feasible, to permit the use of equipment for applying and anchoring mulch.
2. Install needed erosion control measures as required such as dikes, diversions, berms, terraces and sediment barriers.
3. As needed and feasible, loosen compact soil to a minimum depth of 3 inches.

Mulching Materials

1. Dry straw or hay - spread at a rate of 2 1/2 tons per acre.
2. Wood waste, chips, sawdust or bark - spread 2 to 3 inches deep (about 6 to 9 tons per acre).
3. Erosion control matting or netting, such as geotextile, jute, textile and plastic matting and netting - applied in accordance with manufacturers recommendations.
4. Polyethylene film - secured over banks or stockpiled soil material for temporary protection.

Applying and Anchoring Mulch

1. Apply straw or hay mulch uniformly by hand or mechanically. Anchor as appropriate and feasible. It may be pressed into the soil with a disk harrow with the disk set straight or with a special "packer disk". The disk may be smooth or serrated and should be 20 inches or more in diameter and 8 to 12 inches apart. The edges of the disk should be dug enough not to cut the mulch but press it into the soil leaving much of it in an erect position.
2. Spread wood waste uniformly on slopes that are 3:1 and flatter. No anchoring is needed.
3. Commercial matting and netting. Follow manufacturer's specification included with the material.

- B. To conserve moisture and control weeds in nurseries, ornamental beds, around shrubs, and on bar areas on lawns.

Mulching Materials



Use one of the materials given below and apply at thickness indicated.

Material	Depth
1. Grain straw or grass hay	6" to 10"
2. Pine needles	4" to 6"
3. Wood waste (sawdust, bark, chips)	4" to 8"
4. Shredded residues (crops, leaves, etc.)	4" to 8"
5. Completely cover area with black polyethylene film and hold in place by placing soil on the outer edge.	

When using organic mulches, apply 20-30 pounds of nitrogen in addition to the normal amount needed for plant growth to offset the tie up of N by decomposition of mulch.


NOTES:

CONSTRUCTION JOINTS: 12'-0" O.C. MAX. EXPANSION JOINTS: 20'-0" O.C. MAX.




SILT FENCE - TYPE NON-SENSITIVE


Sd1-Ns



FRONT VIEW



CONCRETE WASHOUT



NOTES:

1. ACTUAL LAYOUT DETERMINED IN FIELD.
2. INSTALL CONCRETE WASHOUT SIGN (24"x24", MINIMUM) WITHIN 30' OF THE TEMPORARY CONCRETE WASHOUT FACILITY.
3. TEMPORARY WASHOUT AREA MUST BE AT LEAST 50' FROM A STORM DRAIN, CREEK BANK OR PERIMETER CONTROL.
4. CLEAN OUT CONCRETE WASHOUT AREA WHEN 50% FULL.
5. THE KEY TO FUNCTIONAL CONCRETE WASHOUTS IS WEEKLY INSPECTIONS, ROUTINE MAINTENANCE, AND REGULAR CLEAN OUT.
6. SILT FENCE SHALL BE INSTALLED AROUND PERIMETER OF CONCRETE WASHOUT AREA EXCEPT FOR THE SIDE UTILIZED FOR ACCESSING THE WASHOUT.
7. A ROCK CONSTRUCTION ENTRANCE MAY BE NECESSARY ALONG ONE SIDE OF THE WASHOUT TO PROVIDE VEHICLE ACCESS.

Du DUST CONTROL ON DISTURBED AREAS

PURPOSE

- A. To prevent surface and air movement of dust from exposed surfaces.
- B. To reduce the presence of airborne substances which may be harmful or injurious to human health, welfare, or safety, or to animals or plant life.

Temporary Methods

1. Irrigation. This is generally done as an emergency treatment. Site is sprinkled with water until the surface is wet.
2. Mulching - See Ds1 - Disturbed Area Stabilization (with Mulching only)
3. Vegetative Cover - See Ds2 - Disturbed Area Stabilization

Permanent Methods

1. Permanent Vegetation - See Ds3 - Disturbed Area Stabilization (with Permanent Vegetation)

MULCHING RATES FOR PERMANENT COVER

TYPE OF MULCH	RATE PER ACRE	NOTES
Dry straw	2 Tons	Free of weed seeds
Dry hay	2.5 Tons	Free of weed seeds
Wood Cellulose	500 lbs. 1000 lbs.	Slope less than 3/4:1 Slope greater than 3/4:1
Wood Pulp Fiber	500 lbs. 1000 lbs.	Slope less than 3/4:1 Slope greater than 3/4:1
Service Lespedeza Hay	3 Tons	Containing mature seeds
Pine Straw or Bark	3 inches thick	For bedding Not for seeding
Bituminous treated roving	See DOT specs	Use on slopes, in ditches, or dry waterways.

1. Mulching is not required for temporary grassing.
2. Mulch shall be applied to cover 75% of the soil surface.
3. Sod does not require mulch.

FERTILIZER REQUIREMENTS

TYPE OF SPECIES	YEAR	ANALYSIS OR EQUIVALENT	RATE	N TOP DRESSING RATE	LIME APPLICATION
Cool Season Grasses	First	6-12-12	1500 lbs/ac	50-100 lbs/ac 1*2	2000 lbs/ac
	Second	6-12-12	1000 lbs/ac		
	Maintenance	10-10-10	400 lbs/ac		
Cool Season Grasses and Legumes	First	6-12-12	1500 lbs/ac	0-50 lbs/ac 1*	2000 lbs/ac
	Second	0-10-10	1000 lbs/ac	--	--
	Maintenance	0-10-10	400 lbs/ac	--	--
Ground Covers	First	10-10-10	1500 lbs/ac		
	Second	10-10-10	1000 lbs/ac		
	Maintenance	10-10-10	400 lbs/ac	--	--
Pine Seedlings	First	20-10-5	one 21-gram pallet per seedling placed in the closing hole	--	--
Shrub Lespedeza	First	0-10-10	700 lbs/ac		
	Maintenance	0-10-10	700 lbs/ac 4*	--	--
Temporary Cover Crops Seeded Clone	First	10-10-10	500 lbs/ac	30 lbs/ac 5*	--
Warm Season Grasses	First	6-12-12	1500 lbs/ac	50-100 lbs/ac 2*6*	2000 lbs/ac
	Second	6-12-12	800 lbs/ac	50-100 lbs/ac 2*6*	
	Maintenance	10-10-12	400 lbs/ac	30 lbs/ac	
Warm Season Grasses and Legumes	First	6-12-12	1500 lbs/ac	50 lbs/ac 6*	2000 lbs/ac
	Second	0-10-12	1000 lbs/ac		
	Maintenance	0-10-12	400 lbs/ac		

1. Apply in spring following seeding.
2. Apply in split applications when high rates are used.
3. Apply in 3 split applications.
4. Apply when plants are pruned.
5. Apply to grass species only.
6. Apply when plants grow to height of 2 to 4 inches.

REVISIONS:

1	CITY OF SAVANNAH REVISIONS 1
2	CITY OF SAVANNAH REVISIONS 2

DESIGN PROFESSIONAL:


MARCUS E. SACK
GSWCC LEVEL II # 70248
EXPIRES: 06/14/2026
MARCUS@MESACK.COM

515 NORTH MAIN STREET


P.O. BOX 549

HINESVILLE, GA 31313

TEL: (912) 368-5212



DATE: 3/17/25



MUNICIPALITY:
SAVANNAH

COUNTY:
CHATHAM

OWNER:
JEFF NOTRICA
P.O. BOX 10027
SAVANNAH, GA 31412
(912) 398-2340
ZANDOR@ME.COM

24 HOUR CONTACT:
MARCUS SACK, P.E.
515 N MAIN ST
HINESVILLE, GA 31313
(912) 368-5212
MARCUS@MESACK.COM


1210 DRAYTON
PARKING
IMPROVEMENTS



DETAILS


C500



FILE NO: 2024-45



PLOT DATE: March 17, 2025



REVISIONS:	
1	CITY OF SAVANNAH REVISIONS 1
2	CITY OF SAVANNAH REVISIONS 2
<p>*THIS DRAWING IS AN INSTRUMENT OF SERVICE AND REMAINS THE PROPERTY OF P.C. SIMONOT & ASSOCIATES, INC. AND M.E. SACK ENGINEERING. IT MAY NOT BE COPIED, ALTERED, OR REPRODUCED IN ANY MANNER WITHOUT PERMISSION ON A SIGNED AND SEALED DOCUMENT. THE INFORMATION CONTAINED HEREIN IS INTENDED FOR THE NAMED CLIENT ONLY. IN THE EVENT OF AN ELECTRONIC VERSION (P.C. SIMONOT & ASSOC., INC. AND M.E. SACK ENGINEERING ASSUMES NO RESPONSIBILITY FOR DATA GENERATED, ALTERED OR STAKED FROM THIS DRAWING. IN THE EVENT OF A DISPUTE, HARD COPIES WILL TAKE PRECEDENCE OVER ANY ELECTRONIC MEDIA.*</p>	
<p>DESIGN PROFESSIONAL: MARCUS E. SACK GSWCC LEVEL II # 70248 EXPIRES: 06/14/2026 MARCUS@MESACK.COM</p>	
<p>515 NORTH MAIN STREET P.O. BOX 649 HINESVILLE, GA 31313 TEL: (912) 368-5212</p>	
 <p>DATE: <u>3/17/25</u></p>	
	
<p>MUNICIPALITY: SAVANNAH</p>	
<p>COUNTY: CHATHAM</p>	
<p>OWNER: JEFF NOTRICA P.O. BOX 10027 SAVANNAH, GA 31412 (912) 398-2340 ZANDOR@ME.COM</p>	
<p>24 HOUR CONTACT: MARCUS SACK, P.E. 515 N MAIN ST HINESVILLE, GA 31313 (912) 368-5212 MARCUS@MESACK.COM</p>	
<p>1210 DRAYTON PARKING IMPROVEMENTS</p>	
<p>PRE-DEVELOPED BASIN MAP</p>	
<p>C600</p>	
<p>FILE NO: 2024-45</p>	
<p>PLLOT DATE: March 17, 2025</p>	



DRAWING COMPLETED BY: CHRIS HENDON	REVISIONS:	
	1	CITY OF SAVANNAH REVISIONS 1
	2	CITY OF SAVANNAH REVISIONS 2
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND REMAINS THE PROPERTY OF P.C. SIMONTON & ASSOCIATES, INC. AND M.E. SACK ENGINEERING. IT MAY NOT BE COPIED, ALTERED, OR REPRODUCED IN ANY MANNER WITHOUT PERMISSION ON A SIGNED AND SEALED DOCUMENT. THE INFORMATION CONTAINED HEREIN IS INTENDED FOR THE NAMED CLIENT ONLY. IN THE EVENT OF AN ELECTRONIC VERSION P.C. SIMONTON & ASSOC. INC. AND M.E. SACK ENGINEERING ASSUME 30% RESPONSIBILITY FOR DATA GENERATED, ALTERED OR STAKED FROM THIS DRAWING. IN THE EVENT OF A DISPUTE, HARD COPIES WILL TAKE PRECEDENCE OVER ANY ELECTRONIC MEDIA.		
DESIGN PROFESSIONAL:		
MARCUS E. SACK		
GSWCC LEVEL II # 70248		
EXPIRES: 06/14/2026		
MARCUS@MESACK.COM		
515 NORTH MAIN STREET P.O. BOX 649 HINESVILLE, GA 31313 TEL: (912) 398-5212		
		
DATE: 3/17/24		
		
MUNICIPALITY:		
SAVANNAH		
COUNTY:		
CHATHAM		
OWNER:		
JEFF NOTRICA		
P.O. BOX 10027		
SAVANNAH, GA 31412		
(912) 398-2340		
ZANDOR@ME.COM		
24 HOUR CONTACT:		
MARCUS SACK, P.E.		
515 N MAIN ST		
HINESVILLE, GA 31313		
(912) 368-5212		
MARCUS@MESACK.COM		
1210 DRAYTON PARKING IMPROVEMENTS		
POST-DEVELOPED BASIN MAP		
C601		
FILE NO: 2024-45		
PLOT DATE: March 17, 2025		



LANDSCAPE QUALITY POINTS CALCULATIONS:

REQUIRED LANDSCAPE QUALITY POINTS:
LANDSCAPE QUALITY POINTS = 400 / ACRE
DEVELOPED AREA = .44 ACRES
.44 ACRES X 400 POINTS / ACRE = 176 LANDSCAPE QUALITY POINTS

POINTS REQUIRED = 176
POINTS PROVIDED = 180

PARKING LOT QUALITY POINT CALCULATIONS:





REQUIRED TREE QUALITY POINTS:
 PARKING AREA TREE QUALITY POINTS = 1,200 / ACRE
 PARKING AREA = .44 ACRES
 .44 ACRES X 1,200 POINTS / ACRE = 528 TREE QUALITY POINTS

POINTS REQUIRED = 528
POINTS PROVIDED = 590
(2) PREFERRED LARGE TREE @ 90 TQP = 180 TQP
(13) PREFERRED MEDIUM TREE @ 30 TQP = 390 TQP
(1) EXISTING PALM (16' CT) = 20 TQP




MINIMUM LAND AREA REQUIRED:

20% SHALL BE DEVOTED TO GREEN SPACE
19,166.4 SF X 20% = 3,833.28 SF REQUIRED



3,772.7 SF PROVIDED

Trees									
QU	SYM	Scientific Name	Common Name	QP	TPQ	LQP	Planting Size	Spacing	Comments
3		<i>Cercis canadensis</i>	Redbud	30	90	N/A	2.5"-Cal	as shown	
3		<i>Gordonia aquatica</i>	Loblolly Bay	30	90	N/A	2.5"-Cal	as shown	
7		<i>Magnolia x soulangeana</i>	Sweet Bay Magnolia	30	210	N/A	2.5"-Cal	as shown	
2		<i>Quercus virginiana</i>	Live Oak	90	180	N/A	2.5"-Cal	as shown	

570

Shrub									
QU	SYM	Scientific Name	Common Name	QP	TPQ	LQP	Planting Size	Spacing	Comments
40		Ilex cornuta 'Carissa'	Carissa Holly	3	N/A	120	3-Gal	4' o.c.	
6		Loropetalum chinense var. Rubrum 'Ruby'	Ruby Loropetalum	5	N/A	30	3-Gal	3' o.c.	
10		Rhaphiolepis indica 'Ballerina'	Dwarf Indian Hawthorne	3	N/A	30	3-Gal	3' o.c.	

Shrub

ISSUANCES:	
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND REMAINS THE PROPERTY OF P.C. SHAWNOTON & ASSOCIATES, INC. AND M.E. SACK ENGINEERING. IT MAY NOT BE COPIED, ALTERED, OR REPRODUCED IN ANY MANNER WITHOUT PERMISSION ON A SIGNED AND SEALED DOCUMENT. THE INFORMATION CONTAINED HEREIN IS INTENDED FOR THE NAMED CLIENT ONLY. IN THE EVENT OF AN ELECTRONIC VERSION P.C. SHAWNOTON & ASSOCIATES, INC. AND M.E. SACK ENGINEERING ASSUMES NO RESPONSIBILITY FOR DATA GENERATED, ALTERED OR STAGED FROM THIS DRAWING. IN THE EVENT OF A DISPUTE, HARD COPIES WILL TAKE PRECEDENCE OVER ANY ELECTRONIC MEDIA.	
DESIGN PROFESSIONAL:	
MARCUS E. SACK	
GSWCC LEVEL II #70248	
EXPIRES: 06/14/2026	
MARCUS@MESACK.COM	
515 NORTH MAIN STREET	
P.O. BOX 649	
HINESVILLE, GA 31313	
TEL: (912) 368-5212	
	
DATE: 9/25/24	
	
MUNICIPALITY:	
SAVANNAH	
COUNTY:	
CHATHAM	
OWNER:	
JEFF NOTRICA	
(912) 398-2340	
ZANDOR@ME.COM	
24 HOUR CONTACT:	
MARCUS SACK, P.E.	
515 N MAIN ST	
HINESVILLE, GA 31313	
(912) 368-5212	
MARCUS@MESACK.COM	
1210 DRAYTON PARKING IMPROVEMENTS	
LANDSCAPE PLAN	
L100	
FILE NO: 2024-45	
PLOT DATE: September 25, 2024	

